



Ref. Certif. No.

JP-27333-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product DC Power supply

Name and address of the applicant NIPRON CO LTD
2-57 OHAMA-CHO AMAGASAKI-SHI HYOGO-KEN 660-0095 JAPAN

Name and address of the manufacturer NIPRON CO LTD
2-57 OHAMA-CHO AMAGASAKI-SHI HYOGO-KEN 660-0095 JAPAN

Name and address of the factory NIPRON CO LTD
2-57 OHAMA-CHO AMAGASAKI-SHI HYOGO-KEN 660-0095 JAPAN

Note: When more than one factory, please report on page 2 ☒ [Additional Information on page 2](#)

Ratings and principal characteristics Input: 100-240 Vac, 2.5-1.1 A, 50/60 Hz
Outputs:
+5 Vdc, 10 A; +3.3 Vdc, 7.5 A; +12 Vdc, 8 A; -12 Vdc, 0.3 A; +5 VSB, 1 A

Trademark / Brand (if any) N/A

Customer's Testing Facility (CTF) Stage used

Model / Type Ref. See Page 2

Additional information (if necessary may also be reported on page 2) Additionally evaluated to: EN IEC 62368-1:2020/A11:2020
National Differences specified in the CB Test Report.
☐ [Additional Information on page 2](#)

A sample of the product was tested and found to be in conformity with IEC 62368-1:2018

As shown in the Test Report Ref. No. which forms part of this Certificate E161936-A6071-CB-1 issued on 2023-10-24

This CB Test Certificate is issued by the National Certification Body



- ☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- ☐ UL Solutions (Denko), Borupvang 5A DK-2750 Ballerup, DENMARK
- ☒ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- ☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2023-10-25

Signature:

M. Takagi
Masamichi Takagi



Ref. Certif. No.

JP-27333-UL

Factory(ies):

Nagano Aichi Electric Co., Ltd.
1280 Hara, Kawanakajima-cho, Nagano 381-2282
Japan

Model Detail(s):

PC12U-200Pabcdex ("abcd" can be replaced with any alphanumeric characters and/or hyphens, which denote output configuration (AT or ATX), w/wo +3.3V output, and customer code. "e" can be replaced with either an H or V depending upon fan size. "x" can be replaced with any alphanumeric characters, hyphens, and/or blanks (maximum 50 letters), which denote control number for destination.)

Additional information (if necessary)



- ☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- ☐ UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- ☒ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- ☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2023-10-25

Signature:

Masamichi Takagi