



Ref. Certif. No.

JP-27502-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Power Supply

Name and address of the applicant

NIPRON CO LTD
2-57 OHAMA-CHO AMAGASAKI-SHI HYOGO-KEN 660-0095
JAPAN

Name and address of the manufacturer

NIPRON CO LTD
2-57 OHAMA-CHO AMAGASAKI-SHI HYOGO-KEN 660-0095
JAPAN

Name and address of the factory

NIPRON CO LTD
2-57 OHAMA-CHO AMAGASAKI-SHI HYOGO-KEN 660-0095
JAPAN

Note: When more than one factory, please report on page 2

☒ Additional Information on page 2

Ratings and principal characteristics

See Page 2

Trademark / Brand (if any)

N/A

Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

PCSF-350P may be followed by -ABCD
(Where "ABCD" is any alphanumeric character or blank)

Additional information (if necessary may also be reported on page 2)

Additionally evaluated to: EN IEC 62368-1:2020/A11:2020.
National Differences specified in the CB Test Report.

☐ Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 62368-1:2018

As shown in the Test Report Ref. No. which forms part of this Certificate

E161936-A6072-CB-1 issued on 2024-01-29

This CB Test Certificate is issued by the National Certification Body



- ☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- ☐ UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- ☒ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- ☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2024-01-30

Signature:

M. Takagi
Masamichi Takagi



Ref. Certif. No.

JP-27502-UL

Factory(ies):

NAGANO AICHI ELECTRIC CO LTD
1280 HARA KAWANAKAJIMA-CHO NAGANO 381-2282
JAPAN

NIPRON CO LTD
282-17 Nishiyama Taki-cho Taki-gun Mie 519-2171
JAPAN

Additional Ratings:

Input: 100V-240V~, 3.4-1.4A, 50/60Hz

Rated Output: +3.3Vdc, 14A; +5Vdc, 16A; +12V1, 10A; +12V2, 16A; -12Vdc, 0.5A; +5VSB, 2A
+3.3Vdc and +5Vdc Maximum 90W.
+12V1 and +12V2 Maximum 220W.
Total 250W.

Output-Peak: +3.3Vdc, 20A; +5Vdc, 21A; +12V1, 16A; +12V2, 22A; -12Vdc, 0.8A; +5VSB, 3A
+3.3Vdc and +5Vdc Maximum 120W.
+12V1 and +12V2 Maximum 270W.
Total 350 W.

Additional information (if necessary)



- ☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- ☐ UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- ☒ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- ☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2024-01-30

Signature:

Masamichi Takagi