

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE)
CB SCHEME

CB TEST CERTIFICATE

Product	DC Power Supply
Name and address of the applicant	NIPRON CO LTD 2-57 OHAMA-CHO AMAGASAKI-SHI HYOGO-KEN 660-0095 JAPAN
Name and address of the manufacturer	NIPRON CO LTD 2-57 OHAMA-CHO AMAGASAKI-SHI HYOGO-KEN 660-0095 JAPAN
Name and address of the factory	NIPRON CO LTD 2-57 OHAMA-CHO AMAGASAKI-SHI HYOGO-KEN 660-0095 JAPAN
Note: When more than one factory, please report on page 2	<input checked="" type="checkbox"/> Additional Information on page 2
Ratings and principal characteristics	See Page 2
Trademark / Brand (if any)	None
Type of Customer's Testing Facility (CTF) Stage used	
Model / Type Ref.	HPC1U-400Px (where x maybe maximum 50 characters, any alphanumeric character, hyphen or blank, which denotes control number)
Additional information (if necessary may also be reported on page 2)	Additionally evaluated to EN 62368-1:2014/ A11:2017. National Differences specified in the CB Test Report. <input type="checkbox"/> Additional Information on page 2
A sample of the product was tested and found to be in conformity with	IEC 62368-1:2014
As shown in the Test Report Ref. No. which forms part of this Certificate	E161936-A6005-CB-1 issued on 2019-10-28

This CB Test Certificate is issued by the National Certification Body



- UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
 UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
 UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
 UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2019-10-29

Signature:

Masamichi Takagi

Factories:

NIPRON CO LTD

3249 OIZU INDUSTRIAL PARK IN OYODO KOGYO DANCHI OAZA-YAMAOIZU AZA-NAKAJIMA MEIWA-CHO
TAKI-GUN MIE-KEN 515-0303

JAPAN

Ratings:

AC INPUT: 100V-240V~, 3.8-1.6A, 50/60Hz

DC OUTPUT:

CH1: 3.3Vdc, maximum 16A (peak 20A)

CH2: 5Vdc, maximum 16A (peak 20A)

CH3: 12Vdc, maximum 25A (peak 30A)

CH4: -12Vdc, maximum 0.5A (peak 0.5A)

CH5: 5VSB, maximum 1.5A (peak 2.0A)

Peak: maximum 5 seconds

Interval: 45 seconds

Total Wattage: 305 W maximum (CH1+CH2: 90 W maximum, CH3: 300 W maximum, CH4: 6 W maximum, CH5: 7.5 W maximum)

Peak Wattage: 400 W maximum (CH1+CH2: 120 W maximum, CH3: 360 W maximum, CH4: 6 W maximum, CH5: 10 W maximum)

Additional information (if necessary)



UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2019-10-29

Signature:

Masamichi Takagi