



CN NAME	PIN No.	FUNCTION	CURRENT	WIRE		CONNECTOR TYPE
				COLOR	TYPE	
P1	1	P.G	5mA	ORANGE	UL1007	Housing:90331-1003 (Molex) or equivalent
	2	+5VDC	4A	RED	AWG#18	
	3	+12VDC	3A	YELLOW		
	4	-12VDC	0.5A	BLUE		
	5	COM	3.25A	BLACK		
	6	COM	3.25A	BLACK		
P2	1	COM	4.25A	BLACK	UL1007	Housing:90331-1002 (Molex) or equivalent
	2	COM	4.25A	BLACK	AWG#18	
	3	-5VDC	0.5A	WHITE		
	4	+5VDC	3A	RED		
	5	+5VDC	3A	RED		
	6	+5VDC	3A	RED		
P11	1	COM	5A	BLACK	UL1007	Housing:90331-1009 (Molex) or equivalent
	2	COM	5A	BLACK	AWG#18	
	3	COM	5A	BLACK		
	4	+3.3V	5A	BROWN		
	5	+3.3V	5A	BROWN		
	6	+3.3V	5A	BROWN		
P9	1	+5VS	50mA	VIOLET	UL1007	Housing:CI3303S0010 (CviLux) Δ
	2	ON/OFF	1mA	GRAY	AWG#22	
	3	COM	51mA	BLACK		

出図
6.12.09
ニプロ
技術管理

C版 Δ ×3:2016.12.02 淀 I-280921A
B版 Δ ×1:2014.12.11 淀 I-261217
A版 Δ ×1:2011.07.30 奥平(製品型式変更)

DRAWN BY	CHECKED BY	APPROVED BY	SCALE	MATERIALS	TITLE
柴田	白井	武田	1/1		WH5055 (PS5055) Δ ATX → AT 変換ケーブル
ISSUED	97.12.24	3RD ANGLE PROJECTION		FINISH	DRAWING No. 5055-01-4-050 - C