



Ref. Certif. No.

JP-27655-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	Switching Power Supply
Name and address of the applicant	NIPRON CO LTD 2-57 OHAMA-CHO AMAGASAKI-SHI HYOGO-KEN 660-0095 JAPAN
Name and address of the manufacturer	NIPRON CO LTD 2-57 OHAMA-CHO AMAGASAKI-SHI HYOGO-KEN 660-0095 JAPAN
Name and address of the factory	NIPRON CO LTD 2-57 OHAMA-CHO AMAGASAKI-SHI HYOGO-KEN 660-0095 JAPAN
Note: When more than one factory, please report on page 2	<input checked="" type="checkbox"/> Additional Information on page 2
Ratings and principal characteristics	See Page 2
Trademark / Brand (if any)	N/A
Customer's Testing Facility (CTF) Stage used	
Model / Type Ref.	eNSP-300P-XXYXXXX (X = - or space or 0 to 9 or A to Z. Y = 0 to 9 except 5 and 6 or A to Z.)
Additional information (if necessary may also be reported on page 2)	Additionally evaluated to EN 62368-1:2014/ A11:2017. National Differences specified in the CB Test Report. <input type="checkbox"/> Additional Information on page 2
A sample of the product was tested and found to be in conformity with	IEC 62368-1:2014
As shown in the Test Report Ref. No. which forms part of this Certificate	E161936-A6075-CB-1 issued on 2024-05-10

This CB Test Certificate is issued by the National Certification Body



- UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see [www.ul.com/ncbnames](http://www.ul.com/ncbnames)

Date: 2024-05-10

Signature:

Masamichi Takagi



Ref. Certif. No.

**JP-27655-UL**

**Factory(ies):**

NIPRON CO LTD  
282-17 Nishiyama Taki-cho Taki-gun Mie 519-2171  
JAPAN

**Ratings:**

DC Input: 24Vdc or 23Vdc  
(from BU-300P-24PX Optional Non-stop Unit (Battery module) or Optional Ni-MH Battery Packs)

Rated Output: +5Vdc, 21A; +3.3Vdc, 14A; +12Vdc, 10A; -5Vdc, 0.3A; -12Vdc, 0.8A; +5VS, 1.5A  
(Peak Output: +5Vdc, 30A; +3.3Vdc, 28A; +12Vdc, 15A; -5Vdc, 0.3A; -12Vdc, 0.8A; +5VS, 2.5A)  
Total 203.6Wmax.  
(Peak Power max. 5 seconds, 3 minutes interval.)

**Additional information (if necessary)**



- UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see [www.ul.com/ncbnames](http://www.ul.com/ncbnames)

Date: 2024-05-10

Signature:

Masamichi Takagi