



Ref. Certif. No.

JP-27654-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product Switching Power Supply

Name and address of the applicant NIPRON CO LTD
2-57 OHAMA-CHO AMAGASAKI-SHI HYOGO-KEN 660-0095 JAPAN

Name and address of the manufacturer NIPRON CO LTD
2-57 OHAMA-CHO AMAGASAKI-SHI HYOGO-KEN 660-0095 JAPAN

Name and address of the factory NIPRON CO LTD
2-57 OHAMA-CHO AMAGASAKI-SHI HYOGO-KEN 660-0095 JAPAN

Note: When more than one factory, please report on page 2 ☒ **Additional Information on page 2**

Ratings and principal characteristics See Page 2

Trademark / Brand (if any) N/A

Customer's Testing Facility (CTF) Stage used

Model / Type Ref. eNSP-300P-XXYXXXX
(X = - or space or 0 to 9 or A to Z. Y = 0 to 9 except 5 and 6 or A to Z.)

Additional information (if necessary may also be reported on page 2) Additionally evaluated to EN 62368-1:2014/ A11:2017.
National Differences specified in the CB Test Report.

☐ **Additional Information on page 2**

A sample of the product was tested and found to be in conformity with IEC 62368-1:2014

As shown in the Test Report Ref. No. which forms part of this Certificate E161936-A6075-CB-1 issued on 2024-05-10

This CB Test Certificate is issued by the National Certification Body



- ☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- ☐ UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- ☒ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- ☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2024-05-10

Signature:

M. Takagi
Masamichi Takagi



Ref. Certif. No.

JP-27654-UL

Factory(ies):

NIPRON CO LTD
282-17 Nishiyama Taki-cho Taki-gun Mie 519-2171
JAPAN

Ratings:

AC Input: 100-240Vac, 50/60Hz, 3.1-1.3A.

Rated Output: +5Vdc, 21A; +3.3Vdc, 14A; +12Vdc, 10A; -5Vdc, 0.3A; -12Vdc, 0.8A; +5VS, 1.5A
(Peak Output: +5Vdc, 30A; +3.3Vdc, 28A; +12Vdc, 15A; -5Vdc, 0.3A; -12Vdc, 0.8A; +5VS, 2.5A)
Total 203.6Wmax.
(Peak Power max. 5 seconds, 3 minutes interval.)

Additional information (if necessary)



- ☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- ☐ UL Solutions (Denko), Borupvang 5A DK-2750 Ballerup, DENMARK
- ☒ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- ☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2024-05-10

Signature:

Masamichi Takagi