Removable output harness MH-S0310-500




Model	Stock		
WH-S0310-500	Standard stock		
WH − S 03 10 − 500 ① ② ③ ④ ⑤	① Series name		

Applicable power supply

Desktop PC power supply						
Model	Page	Model	Page			
eNSP3-450P series	B-C2	ePCSA-500P-X2S	B-E22			
eNSP4-500P series	B-C12					

Dimension



Product specification

Items		Specification	Measurement condition	
E	Operating Temp.	-10 to 70°C	Temperature gradient 15°C/H	
Environment	Storage Temp.	-25 to 70°C	Temperature gradient 15°C/H	
	Relative humidity	10 to 95%	No condensation	
Others	Warranty	One year after delivery. However, if any faults belong to us, the defective unit shall be repaired or replaced at our cost.	Provided that the unit shall be operated under normal temp. and humidity, and rating.	

Finout assignment

CONNECTOR TYPE	DINI No.	DINI No.	MAY CLIDDENT	WIDE COLOR	WIDE TVDE	CONNECTOR TYPE
SIG-3		PIN No. MAX CURRENT WIRE COLOR WIRE TYPE CONNECTOR TYPE P12				
Housing: PADP-10V-1-S(JST) or equivalent Terminal: SPH-001T-P0.5L(JST) or equivalent	7	-1	1.6A	BLACK	UL1007 AWG#22	Housing: Cl3103S0000(CviLux) or equivalent Terminal: Cl31T021BE0(CviLux) or equivalent
	9	2	1.6A	BLUE		
	5	3	1.6A	WHITE		
	1	-				
	2	-	1			
	3	-]			
	4	-				
	- 6	-				
	8	-]			
	10					