


Product	Power Supply
Applicant	Nipron Co., Ltd. 2-57 Ohama-cho, Amagasaki-shi, Hyogo-ken 660-0095 Japan
Manufacturer	Nipron Co., Ltd. 2-57 Ohama-cho, Amagasaki-shi, Hyogo-ken 660-0095 Japan
Factory	Nipron Co., Ltd. 2-57 Ohama-cho, Amagasaki-shi, Hyogo-ken 660-0095 Japan
Ratings	Input: 4.8A-1.9A, 100-240V ~ , 50/60Hz
Trade mark	
Model / Type Ref.	eNSP3-450P.....
Principal characteristics	Cl. I, DC-output: Max. 20A 3.3V, max. 22A 5V, max. 22A 12V, max. 0.5A -12V, max. 2A 5VSB The dots '.' in the model name can be '-', space, 0 to 9 or A to Z and denotes shipment difference.
A sample of the product was tested and found to be in conformity with	ITAV EN 62368-1:2014;A11
Replaces	This certificate replaces previous certificate No. P20224284/A1, due to updating component list
Validity	This certificate documents conformity with the standards shown, and also applies as license for use of Nemkos name and certification mark. The certificate and license is valid as long as the applicable conditions are complied with, and provided that any changes to the product are notified to Nemko for acceptance prior to implementation. New standards or amendments to the standards may imply that the product design must be updated and/or that re-testing and re-certification is necessary.
Additional information	Compliance with requirements regarding building-in, protection against electric shock and Electromagnetic Compatibility (EMC) must be checked when the equipment is built-in a completed product or forms a part of a complete system.
Additional model(s)	(4) See page 2

Date of issue 06-06-2022



Sweet Yuan
Certification Department

Nemko Group

Philip Pedersens vei 11, 1366 Lysaker, Norway
TEL +47 22 96 03 30 EMAIL info@nemko.com
ENTERPRISE NUMBER NO974404532

Additional model(s)

Product
Pos. No
Model / Type Ref.
Trade mark (if different from page 1)
Rating
Principal characteristics

Power Supply
1
ePCSA-500P.....

Input: 4.8A-1.9A, 100-240V ~ , 50/60Hz
Cl. I, DC-output: Max. 20A 3.3V, max. 22A 5V, max. 22A 12V, max. 0.5A-12V,
max. 2A 5VSB
The dots '.' in the model name can be '-', space, 0 to 9 or A to Z and denotes
shipment difference.

Product
Pos. No
Model / Type Ref.
Trade mark (if different from page 1)
Rating
Principal characteristics

Power Supply
2
eNSP4-500P.....

Input: 4.8A-1.9A, 100-240V ~ , 50/60Hz
Cl. I, DC-output: Max. 20A 3.3V, max. 22A 5V, max. 22A 12V, max. 0.5A-12V,
max. 2A 5VSB
The dots '.' in the model name can be '-', space, 0 to 9 or A to Z and denotes
shipment difference.

Product
Pos. No
Model / Type Ref.
Trade mark (if different from page 1)
Rating
Principal characteristics

Power Supply
3
ePCSA-500P-X2S3

Input: 4.8A-1.9A, 100-240V ~ , 50/60Hz
Cl. I, DC-output: Max. 20A 3.3V, max. 22A 5V, max. 22A 12V, max. 0.8A
-12V, max. 2A 5VSB

Product
Pos. No
Model / Type Ref.
Trade mark (if different from page 1)
Rating
Principal characteristics

Power Supply
4
eNSP3-450P-S2B-H.V

Input: 4.8A-1.9A, 100-240V ~ , 50/60Hz
Cl. I, DC-output: Max. 26A 3.3V, max. 29A 5V, max. 6A 12V, max. 0.5A -12V,
max. 2A 5VSB

Date of issue 06-06-2022



Sweet Yuan
Certification Department