



Ref. Certif. No.

JP-27071-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product DC Power Supply

Name and address of the applicant NIPRON CO LTD
2-57 OHAMA-CHO AMAGASAKI-SHI HYOGO-KEN 660-0095 JAPAN

Name and address of the manufacturer NIPRON CO LTD
2-57 OHAMA-CHO AMAGASAKI-SHI HYOGO-KEN 660-0095 JAPAN

Name and address of the factory NIPRON CO LTD
2-57 OHAMA-CHO AMAGASAKI-SHI HYOGO-KEN 660-0095 JAPAN

Note: When more than one factory, please report on page 2

Ratings and principal characteristics

Trademark / Brand (if any)

Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

Additional information (if necessary may also be reported on page 2)

A sample of the product was tested and found to be in conformity with

As shown in the Test Report Ref. No. which forms part of this Certificate

☒ Additional Information on page 2

See page 2

None

PCFX-220Px (where x maybe maximum 50 characters, any alphanumeric character, hyphen or blank, which denotes control number)

Additionally evaluated to: EN IEC 62368-1:2020/A11:2020
National Differences specified in the CB Test Report.

☐ Additional Information on page 2

IEC 62368-1:2018

E161936-A6058-CB-1 issued on 2023-05-29

This CB Test Certificate is issued by the National Certification Body



☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
☐ UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
☒ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2023-05-29

Signature:

M. Takagi
Masamichi Takagi



Ref. Certif. No.

JP-27071-UL

Factory(ies):

NIPRON CO LTD
3249 OIZU INDUSTRIAL PARK IN OYODO KOGYO DANCHI OAZA-YAMAOIZU AZA-NAKAJIMA MEIWA-CHO TAKI-GUN
MIE-KEN 515-0303
JAPAN

Ratings:

Input:
100V-240V~, 50/60Hz, 2.5A-1.1A

Output:
CH1: +5 Vdc, 10A (peak 12A)
CH2: +3.3 Vdc, 10A (peak 12A)
CH3: +12 Vdc, 10A (peak 12A)
CH4: -12 Vdc, 0.3A
CH5: +5VSB, 2A

Peak: Maximum 5 seconds
Interval: 45 seconds

Total Wattage: Maximum 170 W
Total Peak Wattage: Maximum 220 W

Additional information (if necessary)



- ☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- ☐ UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- ☒ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- ☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2023-05-29

Signature:

Masamichi Takagi