



Ref. Certif. No.

JP-26884-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

DC Power Supply

Name and address of the applicant

NIPRON CO LTD
2-57 OHAMA-CHO AMAGASAKI-SHI HYOGO-KEN 660-0095
JAPAN

Name and address of the manufacturer

NIPRON CO LTD
2-57 OHAMA-CHO AMAGASAKI-SHI HYOGO-KEN 660-0095
JAPAN

Name and address of the factory

NIPRON CO LTD
2-57 OHAMA-CHO AMAGASAKI-SHI HYOGO-KEN 660-0095
JAPAN

Note: When more than one factory, please report on page 2

☒ Additional Information on page 2

Ratings and principal characteristics

See Page 2

Trademark / Brand (if any)

None

Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

HPC1U-400Px (where x maybe maximum 50 characters, any alphanumeric character, hyphen or blank, which denotes control number)

Additional information (if necessary may also be reported on page 2)

Additionally evaluated to: EN IEC 62368-1:2020/A11:2020
National Difference specified in the CB Test Report.

☐ Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 62368-1:2018

As shown in the Test Report Ref. No. which forms part of this Certificate

E161936-A6054-CB-1 issued on 2023-03-08

This CB Test Certificate is issued by the National Certification Body



- ☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- ☐ UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- ☒ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- ☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2023-03-09

Signature:

M. Takagi
Masamichi Takagi



Ref. Certif. No.

JP-26884-UL

Factory(ies):

NIPRON CO LTD
3249 OIZU INDUSTRIAL PARK IN OYODO KOGYO DANCHI OAZA-YAMAOIZU AZA-NAKAJIMA MEIWA-CHO TAKI-GUN
MIE-KEN 515-0303
JAPAN

Ratings:

AC INPUT: 100V-240V~, 3.8-1.6A, 50/60Hz

DC OUTPUT:

CH1: 3.3Vdc, maximum 16A (peak 20A)

CH2: 5Vdc, maximum 16A (peak 20A)

CH3: 12Vdc, maximum 25A (peak 30A)

CH4: -12Vdc, maximum 0.5A (peak 0.5A)

CH5: 5VSB, maximum 1.5A (peak 2.0A)

Peak: maximum 5 seconds

Interval: 45 seconds

Total Wattage: 305 W maximum (CH1+CH2: 90 W maximum,

CH3: 300 W maximum, CH4: 6 W maximum, CH5: 7.5 W maximum)

Peak Wattage: 400 W maximum (CH1+CH2: 120 W maximum,

CH3: 360 W maximum, CH4: 6 W maximum, CH5: 10 W maximum)

Additional information (if necessary)



- ☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- ☐ UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- ☒ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- ☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2023-03-09

Signature:

Masamichi Takagi