

File E322515

Project 4789076156

November 26, 2019

REPORT

on

POWER CIRCUIT AND MOTOR-MOUNTED APPARATUS

Nipron Co., Ltd.
Hyogo, Japan

Copyright © 2019 UL LLC

UL LLC authorizes the above named company to reproduce this Report only for purposes as described in the Conclusion, provided it is reproduced in its entirety.

DESCRIPTION

PRODUCT COVERED:

- USL, CNL - Power Supply, Models UDD-240-HV/A24V-E00, may be followed by -B.
- USL - Power Supply, Models UDD-240-HV/A24V-E0X, may be followed by -B.
- USL, CNL - Power Supply, Models UDP-240-A24-, followed by E00 or T00, may be followed by any alphanumeric, may be followed by -B.
- USL - Power Supply, Models UDP-240-A24-, followed by E0D or T0D, may be followed by any alphanumeric, may be followed by -B.

GENERAL:

* These devices are open-type switching type power supplies, employing an isolated switching transformer involving a regulating network and a related circuitry. The output is considered as an isolated **secondary** power supply circuit.

These power supplies are intended for use in a controlled environment of a pollution degree 2.

RATING:

Electrical:

Model	Power Input	Power Output
UDD-240 series	135 - 310 Vdc, 1.92 A	24 Vdc, 10 A \$
*UDP-240 series	100 - 240 Vac, 60 Hz, 2.6 A	24 Vdc, 10 A \$

Environmental:

Max. ambient temperature: 70°C \$

Note:

\$ - The derating curve explaining the characteristics between the permissible load and the surrounding air temperature shown in ILLs. 1 thru 3 is the part of the Power Output rating.

NOMENCLATURE

For UDD-240 series:

e.g.	UDD	-	240	-	HV	/	A	24V	-	E	0	0	-B
	----		----		--		--	----		--	--	--	----
	a		b		c		d	e		f	g	h	i

a - Series Name

UDD: High efficiency DIN rail compatible series - DC input;

b - Continuous Output Power

240: 240 W;

c - Type of Input voltage

HV: High voltage;

d - Lightning surge enhancement

A: With arrester;

e - Power Output Voltage

24V: 24 Vdc;

f - Input/ Output Terminal Type

E: European terminal block;

g - Backup function

0: Without backup function;

h - Life Notification Function

0: Without life notification function,

X: With life notification function;

i - DIN rail bracket

blank: Without DIN rail bracket,

-B: With DIN rail bracket.

NOMENCLATURE

For UDP-240 series:

e.g.	UDP	-	240	-	A	24	-	E	0	0	A	-B
	----		----		--	---		--	--	--	--	---
	a		b		c	d		e	f	g	h	i

a - Series Name

UDP: High efficiency DIN rail compatible series;

b - Continuous Output Power

240: 240 W;

c - Lightning surge enhancement

A: With arrester;

d - Power Output Voltage

24: 24 Vdc;

e - Input/ Output Terminal Type

E: European terminal block,

T: Screw terminal block;

f - Backup function

0: Without backup function;

g - Life Notification Function

0: Without life notification function,

D: With life notification function;

h - Modification

Any alphanumeric: Modification code shows the minor modification such as vibration reinforcement to component parts;

i - DIN rail bracket

blank: Without DIN rail bracket,

-B: With DIN rail bracket.

TECHNICAL CONSIDERATIONS (NOT FOR FIELD REPRESENTATIVE'S USE):

* Products designated USL **indicates United States Standards - Listed**, have been investigated using **United States** requirements **as noted in the Test Record**.

* Products designated CNL **indicates Canadian National Standards - Listed**, have been investigated using requirements **as noted in the Test Record**.

copy

CONSTRUCTION DETAILS:

The device shall be constructed in accordance with the following description.

Corrosion Protection - All parts are of corrosion resistant material or are suitably plated, painted or otherwise protected against corrosion.

Tolerances - Unless specified otherwise, all dimensions are nominal.

* Spacings - Spacings were evaluated **using requirements as noted in the Test Record.**

Printed Wiring Board - Unless otherwise specified, all printed wiring boards shall be R/C (ZPMV2/8), rated min. V-1 with a temperature rating of 105°C minimum.

Summary of Figures and Illustrations - The following figures and illustrations are included in this Report.

FIG or ILL. No.	Description
FIG. 1	Models UDP-240-A24-T0D and UDP-240-A24-E0D overall and sides view
FIG. 2	Models UDP-240-A24-T0D and UDP-240-A24-E0D bottom sides view
FIG. 3	Model UDP-240-A24-E0D inside view
ILL. 1	Derating curve in Mounting orientation A
ILL. 2	Derating curve in Mounting orientation B
ILL. 3	Derating curve in Mounting orientation C
ILL. 4	Transformer T1, construction details
ILL. 5	Heatsink for D1, Q101, Q102
ILL. 6	Insulation Sheet located at between Case and Main PWB
*ILL. 7	Insulation Sheet located at around LF1, ZNR1 and ZNR2
ILL. 8	Insulation Sheet located at C17
ILL. 9	Insulation Sheet located at beneath Life detector PWB

Markings - The following markings ink printed, silk-screened, leaser engraved or ink stamped or printed on a label in R/C (PGDQ2/8) or R/C (PGJI2/8) shall be appeared on the device and is visible when the device is mounted singularly but not necessarily visible when mounted side by side:

1. Listee's name;
2. Catalog number;
3. Electrical ratings;
- *4. "See **instruction** manual for derating curve **related to** surrounding air temperature **versus output power**. See **instruction manual for wire size, torque values, environmental condition and other information.**";
5. Maximum surrounding air temperature rating;
- *6. The month and year of manufacture, may be composed in date coding, serial numbers or equivalent;
7. **For models in UDD-24 series, "WARNING: PLEASE USE WIRING RATED FOR AT LEAST 90°C".**

The following markings shall be shipped separately with the device.

1. Temperature rating of the field installed conductors;
2. For models with suffix T in Input, Output Terminals designation, Tightening torque in pound-inches for terminals, 5.31 in-lbs;
3. **The Load factor versus surrounding air temperature derating curve explains the characteristics between the permissible load factor and the surrounding air temperature as the part of the power output rating.**