



Ref. Certif. No.

JP-28660-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	Power supply
Name and address of the applicant	NIPRON CO LTD 2-57 OHAMA-CHO AMAGASAKI-SHI HYOGO-KEN 660-0095 JAPAN
Name and address of the manufacturer	NIPRON CO LTD 2-57 OHAMA-CHO AMAGASAKI-SHI HYOGO-KEN 660-0095 JAPAN
Name and address of the factory	NIPRON CO LTD 282-17 Nishiyama Taki-cho Taki-gun Mie 519-2171 JAPAN <input checked="" type="checkbox"/> Additional Information on page 2
Note: When more than one factory, please report on page 2	
Ratings and principal characteristics	See Pages 2 and 3
Trademark / Brand (if any)	Nipron
Customer's Testing Facility (CTF) Stage used	
Model / Type Ref.	See Page 2
Additional information (if necessary may also be reported on page 2)	Evaluated to National Differences declared for: EN IEC 62368-1:2020/A11:2020 National Differences specified in the CB Test Report. <input type="checkbox"/> Additional Information on page 2
A sample of the product was tested and found to be in conformity with	IEC 62368-1:2018
As shown in the Test Report Ref. No. which forms part of this Certificate	E161936-A6044-CB-2 issued on 2026-05-08

This CB Test Certificate is issued by the National Certification Body



- ☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- ☐ UL Solutions (Denmark), Borupvang 5A DK-2750 Ballerup, DENMARK
- ☒ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- ☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2026-05-08

Signature:

M. Takagi
Masamichi Takagi



Ref. Certif. No.

JP-28660-UL

Factory(ies):

NIPRON CO LTD
2-57 OHAMA-CHO AMAGASAKI-SHI HYOGO-KEN 660-0095
JAPAN

Model Detail(s):

UZP-400-x12y, UZP-400-x24y, UZP-400-x36y, UZP-400-x48y, mUZP-400-x12y, mUZP-400-x24y, mUZP-400-x36y, mUZP-400-x48y (UZP-400 series)

UZP-400/1200P-x24y, UZP-400/1200P-x30y, UZP-400/1200P-x36y, UZP-400/1200P-x40y, UZP-400/1200P-x48y, mUZP-400/1200P-x24y, mUZP-400/1200P-x30y, mUZP-400/1200P-x36y, mUZP-400/1200P-x40y, mUZP-400/1200P-x48y (UZP-400/1200P series)

(where x maybe alphanumeric character or blank, which denotes control number. where y maybe maximum 20 characters, any alphanumeric character, slash, hyphen or blank, which denotes control number)

Ratings:

For UZP-400-x12y, mUZP-400-x12y

Input rating: 100-240V ~, 50-60Hz, 5.0A

Output rating:

- 12Vdc, 26.7A (42 Apeak) (Maximum, at un-forced airflow)

- 12Vdc, 36A (42 Apeak) (Maximum, at forced airflow)

For UZP-400-x24y, mUZP-400-x24y

Input rating: 100-240V ~, 50-60Hz, 5.5A

Output rating:

- 24Vdc, 16.8A (25 Apeak) (Maximum, at un-forced airflow)

- 24Vdc, 21A (25 Apeak) (Maximum, at forced airflow)

For UZP-400-x36y, mUZP-400-x36y

Input rating: 100-240V ~, 50-60Hz, 5.5A

Output rating:

- 36Vdc, 11.2A (16.7 Apeak) (Maximum, at un-forced airflow)

- 36Vdc, 14A (16.7 Apeak) (Maximum, at forced airflow)

For UZP-400-x48y, mUZP-400-x48y

Input rating: 100-240V ~, 50-60Hz, 5.5A

Output rating:

- 48Vdc, 8.4A (12.5 Apeak) (Maximum, at un-forced airflow)

- 48Vdc, 10.5A (12.5 Apeak) (Maximum, at forced airflow)

For UZP-400/1200P-x24y, mUZP-400/1200P-x24y

Input rating: 200-240V ~, 50-60Hz, 2.8A

Output rating:

- 24Vdc, 16.8A (50 Apeak) (Maximum, at un-forced airflow)

- 24Vdc, 21A (50 Apeak) (Maximum, at forced airflow)

Additional information (if necessary)



- ☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- ☐ UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- ☒ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- ☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2026-05-08

Signature:

Masamichi Takagi



Ref. Certif. No.

JP-28660-UL

Ratings (Continued):

For UZP-400/1200P-x30y, mUZP-400/1200P-x30y

Input rating: 200-240V ~, 50-60Hz, 2.8A

Output rating:

- 30Vdc, 13.4A (40 Apeak) (Maximum, at un-forced airflow)

- 30Vdc, 16.8A (40 Apeak) (Maximum, at forced airflow)

For UZP-400/1200P-x36y, mUZP-400/1200P-x36y

Input rating: 200-240V ~, 50-60Hz, 2.8A

Output rating:

- 36Vdc, 11.2A (33.4 Apeak) (Maximum, at un-forced airflow)

- 36Vdc, 14A (33.4 Apeak) (Maximum, at forced airflow)

For UZP-400/1200P-x40y, mUZP-400/1200P-x40y

Input rating: 200-240V ~, 50-60Hz, 2.8A

Output rating:

- 40Vdc, 10A (30 Apeak) (Maximum, at un-forced airflow)

- 40Vdc, 12.5A (30 Apeak) (Maximum, at forced airflow)

For UZP-400/1200P-x48y, mUZP-400/1200P-x48y

Input rating: 200-240V ~, 50-60Hz, 2.8A

Output rating:

- 48Vdc, 8.4A (25 Apeak) (Maximum, at un-forced airflow)

- 48Vdc, 10.5A (25 Apeak) (Maximum, at forced airflow)

Additional information (if necessary)



- ☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- ☐ UL Solutions (Denko), Borupvang 5A DK-2750 Ballerup, DENMARK
- ☒ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- ☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2026-05-08

Signature:

Masamichi Takagi