



| CN NAME | PIN No. | FUNCTION | CURRENT | WIRE | | CONNECTOR TYPE |
|---------|---------|----------|---------|--------|--------|---|
| | | | | COLOR | TYPE | |
| P1 | 1 | P.G | 5mA | ORANGE | UL1007 | Housing:90331-1003 (Molex) or equivalent |
| | 2 | +5VDC | 4A | RED | AWG#18 | |
| | 3 | +12VDC | 3A | YELLOW | | |
| | 4 | -12VDC | 0.5A | BLUE | | |
| | 5 | COM | 3.25A | BLACK | | |
| | 6 | COM | 3.25A | BLACK | | |
| P2 | 1 | COM | 4.25A | BLACK | UL1007 | Housing:90331-1002 (Molex) or equivalent |
| | 2 | COM | 4.25A | BLACK | AWG#18 | |
| | 3 | -5VDC | 0.5A | WHITE | | |
| | 4 | +5VDC | 3A | RED | | |
| | 5 | +5VDC | 3A | RED | | |
| | 6 | +5VDC | 3A | RED | | |
| P11 | 1 | COM | 5A | BLACK | UL1007 | Housing:90331-1009 (Molex) or equivalent |
| | 2 | COM | 5A | BLACK | AWG#18 | |
| | 3 | COM | 5A | BLACK | | |
| | 4 | +3.3V | 5A | BROWN | | |
| | 5 | +3.3V | 5A | BROWN | | |
| | 6 | +3.3V | 5A | BROWN | | |
| P9 | 1 | +5VS | 50mA | VIOLET | UL1007 | Housing:CI3303S0010 (CviLux) Δ |
| | 2 | ON/OFF | 1mA | GRAY | AWG#22 | |
| | 3 | COM | 51mA | BLACK | | |

出図
6.12.09
ニプロ
技術管理

C版 Δ ×3:2016.12.02 淀 I-280921A
B版 Δ ×1:2014.12.11 淀 I-261217
A版 Δ ×1:2011.07.30 奥平(製品型式変更)

| | | | | | |
|----------|------------|----------------------|-------|-----------|--|
| DRAWN BY | CHECKED BY | APPROVED BY | SCALE | MATERIALS | TITLE |
| 柴田 | 白井 | 武田 | 1/1 | | WH5055 (PS5055) Δ ATX → AT 変換ケーブル |
| ISSUED | 97.12.24 | 3RD ANGLE PROJECTION | | FINISH | DRAWING No. 5055-01-4-050 - C |